



*A dedicated range of products for wine labelling*

**TECHNICAL DATA SHEET**

Issued:  
16.05.2014

Product: **CAST COATED WINE K8w WP5**

Code:  
**2541 K8w WP5**

Face Material: **CAST COATED WINE**

Cast gloss coated, woodfree wine paper, wet strength treated

Basis Weight: 80 g/m<sup>2</sup> (ISO 536)

Thickness: 82 µm (ISO 534)

Adhesive: **WP5**

Special permanent acrylic adhesive, specific for labelling of glass wine bottles. Provide good adhesion on slightly damp and cold glass. Complies with the rules and recommendations of BfR (BggVV).

Loop-tack (FTM9 on glass): > 9 N

Peel-adhesion (FTM2 on glass) : > 11 N/25mm

Minimum Application Temperature: > 5°C

Service Temperature: - 25°C to + 75°C

Liner: **K8w**

White supercalendered glassine paper, with good die-cutting and labeling properties. Especially suitable for embossing processes.

Basis Weight: 80 g/m<sup>2</sup> (ISO 536)

Thickness: 71 µm (ISO 534)

Transparency: > 39% (DIN 53147)

Note:

Good performance during immersion in ice-buckets. Testing is recommended.

Shelf-life: 18 months when stored at 22°C and 55% RH

**WARRANTY:**

INTERCOAT materials are manufactured according to highest quality standards and pass stringent quality controls prior to despatch. Any material showing an evident defect of manufacturing will be replaced promptly without charge. The wide range of different applications does not allow to test all possibilities of employment. All statements, technical information and recommendations are based on tests and practical experiences and believed to be reliable but do not constitute a guarantee or warranty. Preliminary tests are recommended for each new application. For any need of advise or technical support the INTERCOAT technical department will be pleased to assist.